



DAY PUBLIC SCHOOL

Chakandra More, Chewara Road, Sheikhpura - 811304 (Bihar)

An English Medium Co-Educational School

(Affiliated to CBSE New Delhi upto Secondary Level, Affiliation No. 331071, School Code No. 66810)

E-mail : davsheikhpura@gmail.com | website : www.davpssheikhpura.com

Ref No. DAV/SHEIKHPURA/20.26/92

Date : 07/07/2026

TENDER NOTICE

SEALED QUOTATIONS ALONGWITH FINANCIAL BID AND TECHNICAL BID ARE INVITED FOR **CONSTRUCTION OF 02 HEAD ROOM & TEMPORARY SHED OVER LIFT SHAFT** AT DAV PUBLIC SCHOOL, SHEIKHPURA TO BE SUBMITTED AT SCHOOL COUNTER LATEST BY **17th JULY 2026** (03:00 PM). BOQ & DESIGN ARE ALSO ATTACHED HEREWITH.

Note: Contractor have to visit the site before filling the bid.

(Sudha Jha)
Principal

(Mr. Niraj Kumar Singh)
Manager

(Mrs. Sabita)
A.R.O.

ABSTRACT OF COST FOR CONSTRUCTION OF HEAD ROOM ON BOTH STAIRS AND TEMPORARY SHED OVER LIFT SHFT AT D.A.V PUBLIC SCHOOL, SHEIKHPURA, BIHAR

Ref no

Date

S NO	SOR	PARTICULARS	QUANTIT Y	RATE	UNIT	AMOUNT
A		1 head room				
			340.0		Sq FT	
		R C C WORK				
1	5.2.2	Reinforced cement concrete work in wall (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts, etc. upt floor five level excluding cost of centring, shuttering, finishin and reinforcement. 1:1.5:3(1 cement: 1.5 coarse sand:3 graded stone aggregate 20mm nominal size)	2.8		Cu m	
2	5.3	R C C work in beams,suspended floors, roofs having slope upto 15, landings,balconiec, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases upto floor five level excludingthe cost of centring shuttering, finishing and reinforement with 1:2:4(1 cement:2 coarse sand:4 graded stone aggregate 20 mm nominal size).	5.5		Cu m	
3	5.4	Providing and laying upto floor five level reinforced cementconcrete in kerbs, steps and the like excluding the cost of centring, shuttering, finishing and reinforcement with 1:2:4(1cement:2 coarse sand:4 graded stone aggregate 20mm nominal size).	0.4		Cu m	
4	5.9	Centring and shuttering including strutting,propping etc. and removal of form for.				
	5.9.3	Suspended floors, roots, landings, balcnies and access platform.	30.6		sq m	
	5.9.4	Shelves (Cost in situ)	1.3		sq m	
	5.9.5	Lintels, beams, plinth bams, griders, bressumers and contilevers	16.3		sq m	
	5.9.6	Columns,Pillars, Piers, Abulments, Posts and Struts	17.9		sq m	
	5.9.7	Stairs,(excluding landings) except spiral-staircaces.	3.3		sq m	
	5.9.19	Weather shade,Chajjas, corbels etc. including edges	0.7		Sq m	

5	5.22	Reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete				
	5.22.7A	Thermo-Mechanically Treated bars TMTC-500 8mm dia	293.4		kg	
	5.22.7B	Thermo-Mechanically Treated bars TMTC-500 10mm dia.	166.9		kg	
	5.22.7C	Thermo-Mechanically Treated bars TMTC-500 12mm dia	26.1		kg	
	5.22.7D	Thermo-Mechanically Treated bars TMT Fe-500-16mm dia.	138.8		kg	
	5.22.7E	Thermo-Mechanically Treated bars TMT Fe-500-20mm dia	342.4		kg	
	5.22.7F	Thermo-Mechanically Treated bars TMT Fe-500-25mm dia	139.2		kg	
		MASONARY WORK				
6	6.1.14A	Brick work with bricks of class designation 100A in superstructure above plinth level upto floor V level in cement mortar 1:6 (1 cement:6 coarse sand)	19.2		Cu m	
7	6.18.4A	Half brick masonry with bricks of class designation 100A in superstructure above plinth level upto floor V level in in :Cement mortar 1:4 (1 cement: 4 coarse sand)	1.6		Sq m	
		FLOORING WORK				
8	11.26.1	Kota stone slab flooring over 25 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and polishing complete 1:4 (1 cement: 4 coarse sand)	32.6		Sq m	
9	11.27	Kota stone slabs 20 mm thick in risers of steps skirting, Dado & pillars laid on 12 mm (average (thick cement mortar 1:3 (1 cement: 3 coarse sand) and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and polishing complete.	2.9		Sq m	
10	11.36	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS : 15622 (Thickness to be specified by the manufacture) of approved make in all colours, shades except burgundy , bottle green , black of any size as approved by Engineer-in-charge in skirting , risers of steps and dados over 12 mm thick bed of cement Motar 1:3(1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm including pointing in white cement mixed with pigment of matching shade complete.	14.3		Sq m	
		PLASTER WORK				
11	13.11.4	12 mm cement plaster of mix:1:6 (1 cement: 6 coarse sand)	106.2		sq m	
12	13.24.2	6 mm cement plaster to ceiling of mix :1:4(1 cement: 4 coarse sand)	32.6		sq m	

CARPENTRY, STEEL, HARDWARE						
13	10.12.1	Providing and fixing steel glazed doors, windows and ventilators of standard rolled steel sections, joints mitred and welded with 15x3 mm lugs 10 cm long with steel lugs embedded in cement concrete blocks 15x10x10 cm of 1:3:6 (1 cement: 3 coarse sand: 6 graded stone aggregate 20 mm nominal size) or with wooden plugs and screws or rawl plugs and screws or with fixing clips or with bolts and nuts as required, including providing and fixing of glass panes with glazing clips and special metal-sash putty of approved make complete including applying a priming coat of approved steel primer, excluding the cost of metal beading and other fitting except	2.2		Sq m	
14	9.5.1.2	Providing and fixing panelled or panelled and glazed shutters for doors, windows and clerestory windows, including ISI marked M.S. pressed butt hinges bright finished of required size with necessary screws, excluding panelling which will be paid for separately, all complete as per direction of Engineer-in-charge. 30 mm thick	1.2		Sq m	
15	9.48.1	Providing and fixing M.S. grills of required pattern in frames of windows etc. with M.S. flats, square or round bars etc. including priming coat with approved steel primer all complete. Fixed to steel windows by welding (1.5 kg per sqft)	60.0		kg	
FINISHING WORK						
16	13.80 A.1	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	88		81.1	
17	13.92	Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade:				
	13.92.1	two or more coats	88		86.4	

18	13.46A	Finishing walls with Acrylic Smooth exterior paint of required shade :				
	13.46A 1	New work (Two or more coat applied @ 1.43 ltr/ 10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm)	30	SqM		
19	13.81 3	Applying priming coat with ready mixed zinc chromate yellow primer of approved brand and manufacture on steel galvanized iron/steel works.	14	SqM		
20	13.93.2	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture	14	SqM		
TOTAL COST OF 1 HEAD ROOM						
COST OF CONSTRUCTION PER SQ FT						
TOTAL COST OF 2 HEAD ROOM						

B		TEMPORARY SHED OVER LIFT SHAFT				
		a temporary shed has been proposed over lift shaft as the final height of it is yet to be determined				
		1 LIFT (13'9" X 6'10")	94.0		SQFT	
21	N A	Rafter/truss (13'9" long) (3 pc)(1.5kg/ft)	62		kg	
22	N A	purlins (6'10" long) (4 pc each) (1.5kg/ft)	41		kg	
23	N A	PVC Shed	8.7		Sq m	
24	N A	Bolts And Fastners (G.I wire, nut boll, s-cup and fastener and lock for gate)				
GRAND TOTAL COST						

SAY TOTAL

NOTE :

rates are inclusive of GST

a temporary shed has been proposed over lift shaft as the final height of it is yet to be determined